

US006815386B1

# (12) United States Patent

Kwong et al.

# (10) Patent No.: US 6,815,386 B1

(45) **Date of Patent:** Nov. 9, 2004

## (54) USE OF PHOSPHATES TO REDUCE SLAG PENETRATION IN CR2O3-BASED REFRACTORIES

# (76) Inventors: Kyei-Sing Kwong, 1450 Queen Ave., SW., Albany, OR (US) 97321; Cynthia P. Dogan, 1450 Queen Ave., SW., Albany, OR (US) 97321; James P. Bennett, 1450 Queen Ave. SW., Albany, OR (US) 97321; Richard E. Chinn, 1450 Queen Ave. SW., Albany, OR (US) 97321-2198; Arthur V. Petty, 1450 Queen Ave., SW., Albany, OR

(US) 97321

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 10/279,120

(22) Filed: Oct. 23, 2002

` /	*	
(51)	Int. Cl. <sup>7</sup> C04	<b>B 35/12</b> ; C04B 35/105
(52)	U.S. Cl 501/2	<b>126</b> ; 501/103; 501/105;
		501/127

# (56) References Cited

#### U.S. PATENT DOCUMENTS

4,039,344 A	*	8/1977	Nishikawa et al 501/89
4,125,409 A	*	11/1978	Friedrichs et al 501/131
4,235,636 A	*	11/1980	Friedrichs et al 501/111
4,507,395 A	o <b>ķ</b> c	3/1985	Jones 501/115
4,823,359 A	*	4/1989	Ault et al 373/137

<sup>\*</sup> cited by examiner

Primary Examiner—Karl Group

(74) Attorney, Agent, or Firm—Mark F. LaMarre; Mark P. Dvorscak; Paul A. Gottlieb

### (57) ABSTRACT

A high-chromium refractory material that provides improved resistance to coal slag penetration is presented. The refractory mixture comprises a blend of chromium oxide, aluminum oxide and phosphates. The refractory mixture may be blended with an aggregate and cured. In addition a phosphorous oxide may be blended with chromium oxide and aluminum oxide and additionally an aggregate. The refractory mixture reduces the rate of coal slag penetration into the surface of the cured refractory.

## 17 Claims, 3 Drawing Sheets

(3 of 3 Drawing Sheet(s) Filed in Color)